

**MATERIAL SAFETY DATA SHEET**

EW HIGH-TEMP ENGINE PAINT ASSORTED COLORS

Printed: 06/28/11

=====

	Hazard Rating:	Health	3
	Least --> Greatest	Flammability	3
Manufacturer:	0 --> 4	Reactivity	1
THE EASTWOOD COMPANY		Personal Protection	J
263 SHOEMAKER ROAD			
POTTSTOWN, PA 19464			
Phone: 800-345-1178	EMERGENCY TELEPHONE:	800-424-9300	

SECTION I: PRODUCT IDENTIFICATION

Product Code: 51615ZP, 51616ZP, 51617ZP, 51618ZP, 51619ZP, 51620ZP, 51621ZP, 51622ZP, 51623ZP, 51624ZP, 51625ZP, 51626ZP, 51627ZP, 51628ZP, 51629ZP, 51630ZP, 51631ZP, 51632ZP, 51633ZP, 51634ZP, 51682ZP, 51683ZP, 13786ZP

Product Name: EW HIGH-TEMP ENGINE PAINT

Product(s): EW HIGH-TEMP ENGINE PAINT

Product Class: PAINT CAS Number: NA

SECTION IIA: HAZARDOUS INGREDIENTS (To Nearest 1.00%)

INGREDIENT	CAS Number	51615ZP		51616ZP		51621ZP		51627ZP	
		% by Weight	% by Volume	% by Weight	% by Volume	% by Weight	% by Volume	LEL % (V)	Vapor Pressure
1. SILICONE ALKYD	MIXTURE	88.00	86.00	88.00	86.00	88.00	86.00	1.0	.30
2. ALUMINUM	MIXTURE	1.00	.42					1.0	.40
3. MINERAL SPIRITS	8052-41-3	9.00	10.00	9.00	10.00	9.00	10.00	1.0	2.00

NA = Not Applicable; NE = Not Established

SECTION IIB: OCCUPATIONAL EXPOSURE LIMITS

	----OSHA PEL's-----		-----ACGIH TLV's-----			
Ingr. #	OSHA ppm	OSHA mg/m3	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3
1.	500.000	NA	500.000	NA	NA	NA
2.	500.000	NA	500.000	NA	NA	NA
3.	100.000	NA	100.000	100.000	100.000	NA

NA = Not Applicable; NE = Not Established

SECTION III: PHYSICAL DATA

Boiling Range (degrees F): 282.00 - 286.00 Pounds per Gallon: 7.77

Vapor Density: HEAVIER THAN AIR Evaporation Rate: SLOWER THAN ETHER

Solubility in Water: NIL

Volatiles (%)		by Weight	by Volume
	Total	45.79	52.29
	Exempt VOC	.00	.00
	Non-exempt	45.79	52.29

VOC wt/gal: 3.56 lbs non-exempt solvent per adjusted gallon

Appearance: Liquid, Assorted Colors

## MATERIAL SAFETY DATA SHEET

EW HIGH-TEMP ENGINE PAINT ASSORTED COLORS

Printed: 06/28/11

## SECTION IV: FIRE AND EXPLOSION HAZARD DATA

## Flammability Classification:

OSHA: COMB DOT: COMB

Flash Point: 105 (Method: Tcc)

UEL: 7

Extinguishing Media: CO2/FOAM

## Unusual Fire and Explosion Hazards

THIS MATERIAL MAY BE IGNITED BY HEAT, SPARKS, FLAME OR STATIC ELECTRICITY. KEEP CONTAINERS CLOSED WHEN NOT IN USE. ISOLATE FROM HEAT, SPARKS, PILOT LIGHTS, SMOKING MATERIALS AND OTHER SOURCES OF IGNITION.

## Special Firefighting Procedures

THE USE OF SCBA IS RECOMMENDED FOR FIREFIGHTERS. WATER SPRAY MAY BE USEFUL IN COOLING CONTAINERS EXPOSED TO HEAT AND FLAME. AVOID SPREADING BURNING LIQUID WITH WATER USED FOR COOLING PURPOSES.

FIGHT AS VOLATILE LIQUID FIRE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

## SECTION V: HEALTH HAZARD DATA

## Effects of Overexposure

DIZZINESS, NAUSEA, VOMITING, LOSS OF COORDINATION, AND FATIGUE.

## Medical Conditions Prone to Aggravation by Exposure

ASTHMA, HEART CONDITION.

## Primary Routes of Entry into the Body, and Effects

MOUTH, SKIN, LUNGS.

## EMERGENCY FIRST-AID PROCEDURES

SKIN CONTACT: FLUSH WITH WATER. IF REDNESS PERSISTS SEEK MEDICAL ATTENTION.

INHALATION: IF RESPIRATORY SYMPTOMS DEVELOP, REMOVE VICTIM FROM SOURCE OF EXPOSURE TO FRESH AIR. IF SYMPTOMS PERSIST SEEK MEDICAL ATTENTION

INGESTION: SEEK EMERGENCY MEDICAL ATTENTION

## SECTION VI: REACTIVITY DATA

Stability: STABLE Hazardous Polymerization WILL NOT OCCUR.

## Hazardous Decomposition Products

CO2

## Conditions to Avoid

HEAT, SPARKS, OPEN FLAMES, STATIC ELECTRICITY

## Incompatibilities (Materials to Avoid)

MATERIAL SAFETY DATA SHEET

EW HIGH-TEMP ENGINE PAINT ASSORTED COLORS

Printed: 06/28/11

=====

SECTION VII: SPILL OR LEAK PROCEDURES: WASTE DISPOSAL

Steps to be taken if Material is Leaked or Spilled  
STAY UPWIND. REMOVE SOURCE OF IGNITION. KEEP OUT OF DRAINS, SEWERS, WATERWAYS  
USE ABSORBENT PADS

Waste Disposal Methods

DISPOSE PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY, STATE, AND FEDERAL  
REGULATIONS.

-----

SECTION VIII: SAFE HANDLING AND USE INFORMATION

Respiratory Protection

APPROVED ORGANIC SUPPLIED AIR RESPIRATOR

Ventilation

MECHANICAL EXPLOSIONPROOF

Protective Gloves

YES

Eye Protection

YES

Other Protective Equipment

IMPERVIOUS CLOTHING

Hygienic Practices

WASH BEFORE EATING.

-----

SECTION IX: SPECIAL PRECAUTIONS

Handling and Storing

KEEP IN COOL PROPERLY VENTILATED EXPLOSION PROOF AREA.

Other Precautions

KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. USE APPROVED GROUNDING  
EQUIPMENT TO AVOID STATIC SPARKS.

NOTE: THIS PRODUCT CONTAINS XYLOL AND IS SUBJECT TO THE REPORTING  
REQUIREMENTS OF SARA 313 AND 40 CFR 372

WARNING! This product contains chemical substance(s) known to the state of  
California to cause cancer and birth defects or other reproductive harm.

Reason for revision: Section 1 revised to include additional product numbers.

DISCLAIMER: THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE  
PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AS OF THIS DATE.  
EASTWOOD MAKES NO REPRESENTATION AS TO THE COMPLETENESS OR ACCURACY  
THEREOF. INFORMATION IS SUPPLIED UNDER THE CONDITION THAT THE RECIPIENT  
WILL MAKE HIS OWN DETERMINATION AS TO ITS SUITABILITY FOR THEIR  
INTENDED PURPOSE, PRIOR TO USE.

=====

END OF MSDS

=====